International Journal of Research Publications in Engineering, Technology and Management (IJRPETM)

|www.ijrpetm.com | ISSN: 2454-7875 | editor@ijrpetm.com |A Bimonthly, Peer Reviewed & Scholarly Journal|

||Volume 9, Issue 4, July – August 2026||

DOI:10.15662/IJRPETM.2026.0904011

Cognitive Digital Resilience Through Generative AI for Cloud Applications and Real-Time Security Intelligence

Rajabhushanam .C

Professor, Department of Computer Science Engineering, Bharath Institute of Higher Education and Research, Chennai, India

Publication History: Received: 10.05.2026; Revised: 27.06.2026; Accepted: 01.07. 2026; Published: 12.07.2026.

ABSTRACT: Cloud applications increasingly operate across distributed, dynamic, and interconnected infrastructures where conventional security and resilience mechanisms may struggle to respond to rapidly changing threats. This research proposes a cognitive digital resilience framework that integrates Generative Artificial Intelligence (GenAI), cloud observability, intelligent threat detection, behavioral analytics, and automated security intelligence to strengthen the resilience of modern cloud applications. The proposed framework continuously collects telemetry from applications, infrastructure, identities, APIs, containers, networks, and cloud services and transforms heterogeneous information into contextual security intelligence. Machine learning techniques identify anomalous behaviors, while GenAI analyzes correlated events, generates incident explanations, supports threat investigation, and recommends adaptive mitigation strategies. A cognitive decision layer integrates historical incidents, threat intelligence, application context, vulnerability information, and operational policies to prioritize risks and coordinate defensive responses. The methodology incorporates data preprocessing, feature engineering, anomaly detection, contextual threat correlation, retrieval-augmented generative analysis, resilience assessment, and experimental validation. Evaluation considers detection accuracy, false-positive rate, response latency, resilience recovery time, intelligence quality, scalability, and computational overhead. The framework aims to shift cloud security from reactive monitoring toward continuous cognitive resilience by enabling applications and security operations to understand evolving conditions, anticipate potential disruptions, and coordinate appropriate responses. The research provides an integrated foundation for improving security visibility, operational continuity, and adaptive defense in complex cloud application environments.

KEYWORDS: Generative AI, Cognitive Digital Resilience, Cloud Applications, Real-Time Security Intelligence, Cloud Security, Threat Detection, Artificial Intelligence, Security Analytics, Anomaly Detection, Automated Response, Cloud Observability, Cyber Resilience

I. INTRODUCTION

Cloud computing has become a fundamental foundation for modern enterprise applications because it provides elastic resources, distributed services, rapid deployment, global accessibility, and flexible infrastructure management. However, the same characteristics that make cloud applications highly scalable also create complex security and resilience challenges. Applications increasingly depend on microservices, containers, APIs, serverless functions, distributed databases, identity platforms, and third-party services, resulting in continuously changing relationships among users, workloads, applications, and infrastructure components. Security incidents can therefore propagate rapidly across interconnected resources, while conventional monitoring approaches may generate fragmented alerts without sufficient contextual understanding. Organizations must simultaneously address credential abuse, application vulnerabilities, malicious API activity, configuration errors, supply-chain threats, data exposure, ransomware, and service disruptions. Traditional rule-based monitoring is effective for known patterns but may be less effective against novel and rapidly evolving behaviors. Digital resilience consequently requires more than preventing attacks; it requires the ability to continuously observe the environment, interpret changing conditions, adapt defensive controls, recover from disruptions, and maintain essential business services. Artificial intelligence provides opportunities to strengthen these capabilities through behavioral analysis, anomaly detection, predictive intelligence, and automated decision support. Generative AI further expands this potential by transforming large volumes of technical security information into contextual explanations, investigation narratives, and actionable intelligence.

|www.ijrpetm.com | ISSN: 2454-7875 | editor@ijrpetm.com |A Bimonthly, Peer Reviewed & Scholarly Journal|

||Volume 9, Issue 4, July – August 2026||

DOI:10.15662/IJRPETM.2026.0904011

Cognitive digital resilience represents an integrated approach in which cloud systems continuously perceive operational and security conditions, reason about emerging risks, and support adaptive responses while maintaining organizational policies and governance requirements. The proposed research develops such a capability by integrating GenAI with cloud observability, machine learning, threat intelligence, application telemetry, and resilience management. The framework establishes a continuous intelligence cycle involving telemetry collection, normalization, behavioral analysis, threat correlation, cognitive interpretation, response recommendation, and resilience assessment. GenAI functions as an intelligence interface capable of synthesizing security events, identifying relationships among seemingly independent activities, explaining potential attack scenarios, generating investigation queries, and recommending appropriate defensive actions. Retrieval-based grounding connects the generative model to validated enterprise information, including security policies, application dependencies, threat intelligence, vulnerability records, and historical incidents. The research investigates whether this integrated approach can improve real-time security intelligence while supporting application availability and recovery. Particular attention is given to detection accuracy, response latency, false-positive reduction, contextual intelligence, scalability, explainability, and resilience recovery. By combining security intelligence with operational resilience, the proposed framework seeks to provide a systematic foundation for cloud applications that can continuously detect, understand, adapt to, and recover from evolving security disruptions.

II. LITERATURE REVIEW

Cloud application security research has traditionally focused on intrusion detection, vulnerability management, security information and event management, access control, endpoint monitoring, and cloud-native security mechanisms. These approaches provide important preventive and detective capabilities but often operate through predefined rules and isolated monitoring functions. The expansion of cloud-native architectures has increased the volume and diversity of telemetry generated by applications, containers, orchestration platforms, APIs, identities, databases, and infrastructure services. Machine learning has consequently become increasingly relevant to cloud security because it can identify behavioral patterns and anomalies within large-scale telemetry. Supervised learning can classify known malicious activities, whereas unsupervised and semi-supervised methods can identify deviations without requiring comprehensive attack labels. Deep learning models can capture complex nonlinear relationships among security events and application behaviors. However, machine-learning security systems can experience challenges involving data imbalance, concept drift, adversarial manipulation, model explainability, and limited availability of representative enterprise datasets. These limitations indicate the need for architectures that combine statistical detection with contextual reasoning and continuously updated intelligence.

Digital resilience extends traditional cybersecurity by emphasizing an organization's ability to anticipate, withstand, respond to, and recover from disruptive events. Within cloud environments, resilience is closely associated with observability, redundancy, fault tolerance, incident response, workload isolation, backup strategies, automated recovery, and continuous risk assessment. Security resilience requires understanding both malicious and non-malicious disruptions because configuration errors, service failures, resource exhaustion, and cyberattacks can interact to affect application availability. Threat intelligence platforms contribute contextual information by associating security events with indicators of compromise, vulnerabilities, adversarial behaviors, and known attack techniques. Graph-based analytics can further model relationships among identities, workloads, applications, network resources, and attack activities. Autonomous security systems build upon these capabilities by continuously collecting and correlating intelligence and initiating bounded analytical workflows. However, autonomy must be controlled because inaccurate correlations or poorly configured automated responses may introduce operational risks. Consequently, resilience-oriented security architectures require policy enforcement, confidence evaluation, auditability, and human oversight for high-impact decisions.

Generative AI and large language models have introduced new capabilities for security operations by enabling natural-language analysis of complex technical information. GenAI can summarize incidents, generate threat narratives, explain security alerts, assist threat hunting, formulate queries, analyze configuration information, and support security analysts during investigations. Retrieval-augmented generation can improve contextual grounding by connecting generative models with trusted organizational documentation, threat intelligence repositories, historical incidents, and current telemetry. These capabilities are particularly relevant to real-time security intelligence because security teams frequently need to synthesize information from multiple sources under time constraints. Nevertheless, generative systems introduce risks including hallucinated conclusions, unsupported recommendations, prompt injection, sensitive-data exposure, and inconsistent outputs. Therefore, GenAI should operate within controlled security architectures where outputs are grounded in verified evidence and validated against policies. Existing research demonstrates the value of AI-based detection, cloud observability, threat intelligence, and generative security assistance individually, but opportunities

|www.ijrpetm.com | ISSN: 2454-7875 | editor@ijrpetm.com |A Bimonthly, Peer Reviewed & Scholarly Journal|

||Volume 9, Issue 4, July – August 2026||

DOI:10.15662/IJRPETM.2026.0904011

remain for integrating these capabilities into a unified cognitive resilience framework. This research addresses that gap by connecting real-time cloud telemetry, intelligent threat analytics, GenAI reasoning, and resilience-oriented response mechanisms.

III. RESEARCH METHODOLOGY

Research Design and Cognitive Resilience Architecture: The research adopts a design-and-evaluation methodology to develop a cognitive digital resilience architecture for cloud applications. The proposed framework is organized into six major layers: telemetry acquisition, security data processing, intelligent behavioral analytics, contextual threat intelligence, generative cognitive intelligence, and adaptive resilience orchestration. The telemetry acquisition layer continuously collects application logs, API transactions, authentication events, network flows, container activities, Kubernetes events, infrastructure metrics, database events, cloud configuration changes, vulnerability information, and system-performance indicators. The data-processing layer converts heterogeneous records into a unified event representation through parsing, normalization, deduplication, timestamp synchronization, and schema alignment. The behavioral analytics layer establishes dynamic baselines for users, applications, workloads, APIs, and infrastructure resources. Machine-learning models analyze behavioral deviations and identify suspicious activity, unusual resource consumption, anomalous authentication sequences, unexpected network communication, and abnormal application interactions. The contextual threat-intelligence layer enriches detected events using vulnerability information, indicators of compromise, attack techniques, asset criticality, historical incidents, and external intelligence. GenAI provides the cognitive interpretation layer, transforming correlated evidence into incident explanations, attack narratives, investigation hypotheses, and response recommendations. Finally, the resilience orchestration layer connects validated security intelligence with operational controls such as workload isolation, credential revocation, access-policy modification, service failover, traffic restriction, backup restoration, and incident escalation. The architecture incorporates continuous feedback so that response outcomes and analyst validation can contribute to future detection and decision processes. Automated actions are governed by predefined policies and confidence thresholds, while high-impact operations require human authorization.

Data Acquisition, Preparation, and Feature Engineering: The experimental environment represents a distributed enterprise cloud application containing interconnected services, APIs, identity components, databases, containers, and cloud infrastructure. Both normal operational activity and controlled security scenarios are introduced to evaluate the framework. Relevant scenarios include suspicious authentication, credential misuse, privilege escalation, anomalous API activity, malicious configuration changes, unusual workload execution, lateral movement, vulnerability exploitation, unauthorized data access, denial-of-service behavior, and simulated data-exfiltration activity. Operational disruptions such as resource exhaustion and service degradation are also considered because digital resilience must address security and availability simultaneously. Raw telemetry is transformed into structured security events containing timestamp, source, destination, identity, application, workload, action, protocol, resource, privilege level, event frequency, and contextual risk attributes. Data preprocessing removes duplicate events, malformed records, inconsistent timestamps, irrelevant entries, and excessive operational noise. Feature engineering generates behavioral, temporal, relational, and contextual features. Behavioral features include authentication frequency, failed-login ratios, API request distributions, access-pattern changes, workload execution frequency, and resource-consumption variation. Temporal features capture event sequences, unusual activity windows, burst behavior, and deviations from historical baselines. Relational features describe communication between identities, applications, workloads, APIs, and infrastructure resources. Contextual features incorporate asset criticality, vulnerability exposure, threat-intelligence confidence, application dependency, and business-service importance. Data normalization and appropriate encoding are applied before machine-learning analysis. Training, validation, and testing datasets are separated according to time or scenario to minimize information leakage. Where sensitive enterprise information is involved, anonymization and synthetic identifiers are applied. Rare security events are preserved carefully because aggressive balancing can distort realistic attack distributions.

International Journal of Research Publications in Engineering, Technology and Management (IJRPETM)

|www.ijrpetm.com | ISSN: 2454-7875 | editor@ijrpetm.com |A Bimonthly, Peer Reviewed & Scholarly Journal|

||Volume 9, Issue 4, July – August 2026||

DOI:10.15662/IJRPETM.2026.0904011




FIG1: Framework for Cognitive Digital Resilience Utilizing Generative AI and Real-Time Security Intelligence for Cloud Applications

Intelligent Threat Detection and Generative Security Intelligence: The analytical stage uses a layered detection strategy combining anomaly detection, classification, temporal analysis, correlation, and contextual threat intelligence. Baseline behavioral models establish normal operating profiles for identities, applications, APIs, containers, and cloud resources. Deviations from these profiles generate anomaly scores that are evaluated together with known threat indicators and application context. Supervised machine-learning models can classify known security scenarios, while unsupervised models identify previously unobserved behaviors. Sequential analysis examines event chains because sophisticated attacks may involve multiple low-severity activities that become significant only when considered collectively. A relationship graph represents interactions among users, services, applications, workloads, network resources, vulnerabilities, and security events. This graph supports identification of suspicious paths, privilege transitions, and lateral movement. The threat-intelligence engine enriches detected events using indicators of compromise, vulnerability relationships, attack techniques, and historical incident patterns. A contextual risk score is calculated using behavioral deviation, asset criticality, threat confidence, vulnerability severity, attack-stage relationships, and potential business impact. GenAI is introduced after evidence aggregation rather than receiving unrestricted raw telemetry. A retrieval-augmented generation mechanism supplies the model with validated security events, enterprise policies, application documentation, threat intelligence, and historical incident information. The model is instructed to distinguish observed evidence from inferred hypotheses and to produce evidence-grounded outputs. Generated intelligence includes incident summaries, affected assets, probable attack sequences, investigation questions, recommended queries, potential containment strategies, and explanations of why a particular event requires attention. Output validation checks generated recommendations against structured evidence and security policies. Autonomous agents may conduct bounded activities such as intelligence enrichment, evidence collection, query generation, and incident summarization, whereas irreversible actions remain subject to authorization controls.

Experimental Evaluation, Resilience Measurement, and Validation: The proposed framework is evaluated through controlled experiments involving baseline monitoring, machine-learning-based detection, contextual threat intelligence, and the integrated GenAI-enabled cognitive resilience architecture. Quantitative evaluation measures precision, recall, F1-score, false-positive rate, false-negative rate, detection latency, incident-correlation accuracy, response latency, and computational overhead. Digital resilience is evaluated using recovery time, service continuity, disruption duration, containment effectiveness, and the percentage of critical application functions maintained during simulated security incidents. Mean time to detect and mean time to investigate are measured to determine whether cognitive generative

|www.ijrpetm.com | ISSN: 2454-7875 | editor@ijrpetm.com |A Bimonthly, Peer Reviewed & Scholarly Journal|

||Volume 9, Issue 4, July – August 2026||

DOI:10.15662/IJRPETM.2026.0904011

intelligence reduces the operational workload associated with complex incidents. Scalability experiments progressively increase telemetry volume, number of applications, concurrent workloads, monitored identities, and simultaneous security events. Ablation studies remove individual components such as behavioral analytics, threat-intelligence enrichment, graph correlation, retrieval augmentation, or GenAI reasoning to determine their contribution to overall performance. Robustness experiments introduce noisy telemetry, incomplete indicators, changing application behavior, previously unseen attack patterns, conflicting intelligence, and rapidly changing cloud resources. GenAI evaluation examines factual consistency, evidence grounding, hallucination frequency, recommendation relevance, response coherence, and resistance to misleading input. Resilience validation additionally examines whether recommended actions preserve application availability while containing security threats. Governance validation evaluates authentication, authorization, audit logging, data minimization, model-output validation, policy enforcement, and human approval mechanisms. Repeated experiments are used to reduce dependence on individual test cases, while statistical analysis compares the resulting performance measurements. Qualitative evaluation examines the usefulness and clarity of generated incident explanations for security analysts. The final assessment combines security-detection performance with resilience and operational measurements, thereby evaluating whether the proposed approach can simultaneously improve threat visibility, intelligence quality, response coordination, and service continuity. This methodology provides a structured basis for determining the practical value of integrating GenAI with cloud observability and autonomous security intelligence while maintaining appropriate safeguards for enterprise cloud operations.

IV. RESULTS AND DISCUSSION

The proposed cognitive digital resilience framework demonstrated how Generative Artificial Intelligence (GenAI) can strengthen the security, reliability, and adaptive capabilities of cloud-based applications through continuous security intelligence. The framework integrates cloud telemetry, application logs, identity events, network activities, infrastructure metrics, vulnerability information, and threat intelligence into a unified analytical layer. The cognitive intelligence component continuously evaluates these heterogeneous signals to identify abnormal behavior, emerging risks, service degradation, and potential security incidents. Unlike conventional monitoring mechanisms that primarily depend on predefined thresholds and signatures, the proposed approach analyzes relationships among multiple events and generates contextual interpretations. The integration of GenAI enables security information to be converted into meaningful incident narratives, risk explanations, and response recommendations. The results indicate that this capability improves security visibility across distributed cloud environments because individual events can be correlated into broader behavioral patterns. For example, an unusual authentication event combined with suspicious API activity and abnormal resource consumption can be interpreted as a potentially coordinated security incident rather than several unrelated alerts. This cognitive correlation contributes to earlier recognition of complex attack scenarios and provides security teams with richer contextual information for investigation and decision-making.

The evaluation further indicated that cognitive intelligence can improve the responsiveness and operational efficiency of cloud security monitoring. Continuous analysis of telemetry enables the framework to identify deviations from established behavioral patterns while dynamically considering application criticality, user context, workload characteristics, and historical activity. GenAI assists by summarizing detected incidents, identifying potentially affected resources, explaining observed attack indicators, and recommending appropriate mitigation actions. This reduces the amount of manual effort required to interpret large volumes of security information. The framework also supports proactive security intelligence by generating threat-hunting hypotheses from emerging behavioral patterns and examining related cloud activities for additional evidence. Another important observation was the ability to connect security intelligence with operational resilience. Security events affecting application availability, resource utilization, configuration integrity, or service dependencies can be analyzed together, enabling organizations to understand both cybersecurity and service-continuity implications. However, the results also reveal limitations associated with GenAI-generated analysis. Incomplete telemetry, ambiguous events, previously unseen behaviors, and insufficient contextual information can lead to inaccurate interpretations or inappropriate recommendations. Consequently, generated recommendations should be validated against trusted security policies and operational controls before high-impact actions are executed. Human supervision remains particularly important for actions involving sensitive identities, critical workloads, production configurations, and irreversible infrastructure changes.

Overall, the findings demonstrate that combining cognitive computing principles with GenAI can move cloud security monitoring from reactive event processing toward continuous digital resilience management. The framework does not treat security as an isolated operational function; instead, it connects threat intelligence with application reliability, infrastructure health, identity behavior, and business-critical cloud services. This integrated perspective enables

|www.ijrpetm.com | ISSN: 2454-7875 | editor@ijrpetm.com |A Bimonthly, Peer Reviewed & Scholarly Journal|

||Volume 9, Issue 4, July – August 2026||

DOI:10.15662/IJRPETM.2026.0904011

organizations to assess how security events may propagate across interconnected cloud resources and to prioritize incidents according to contextual risk. The cognitive layer can continuously update its understanding as new observations become available, allowing security intelligence to evolve alongside changing workloads and attack behaviors. The approach is particularly applicable to hybrid and multi-cloud environments where applications frequently change their deployment locations, dependencies, configurations, and resource requirements. Nevertheless, scalability, model governance, telemetry quality, computational overhead, and integration complexity remain important implementation considerations. The results suggest that GenAI should operate as an intelligent augmentation layer supported by established security controls rather than functioning as an unrestricted autonomous authority. With appropriate validation, access control, explainability, and monitoring mechanisms, cognitive GenAI can provide a foundation for resilient cloud applications capable of detecting, understanding, and responding to security risks continuously.

V. CONCLUSION

This research presented a cognitive digital resilience approach that integrates Generative AI with continuous cloud security intelligence to improve the protection and operational resilience of modern cloud applications. Traditional cloud security architectures often rely on isolated monitoring tools, predefined rules, static signatures, and manual incident analysis. Such approaches can become increasingly difficult to manage as enterprise applications become distributed across containers, microservices, APIs, serverless platforms, hybrid clouds, and multi-cloud infrastructures. The proposed framework addresses these challenges by combining heterogeneous cloud telemetry with intelligent behavioral analysis and GenAI-supported contextual reasoning. The results demonstrate that this combination can improve the interpretation of complex security events by correlating seemingly independent observations and transforming them into structured security narratives. GenAI additionally provides capabilities for incident summarization, threat explanation, investigative assistance, and remediation recommendation. These capabilities can help security professionals understand rapidly changing cloud environments while reducing the manual effort required to process large volumes of telemetry. The cognitive approach also extends security monitoring beyond simple threat detection by considering application availability, infrastructure behavior, identity activity, and service dependencies as interconnected components of digital resilience.

The findings establish that effective cloud resilience requires continuous intelligence, contextual decision-making, and coordinated security and operational controls. A GenAI-enabled cognitive layer can provide organizations with an adaptive mechanism for analyzing emerging risks and supporting proactive security operations. However, the benefits of such systems depend on trustworthy data, carefully controlled automation, reliable threat intelligence, model validation, and appropriate governance. GenAI-generated outputs may contain uncertainty, particularly when security events are novel or contextual information is incomplete. Therefore, high-impact decisions should incorporate confidence assessment, policy validation, authorization controls, and human review. The framework should be considered an intelligent decision-support and resilience mechanism rather than a replacement for established security technologies or expert security personnel. Future implementations can strengthen its capabilities through retrieval-augmented intelligence, explainable AI, federated learning, graph-based threat modeling, adversarial robustness, and continuous model evaluation. Integration with zero-trust security, automated compliance management, confidential computing, and cloud-native observability can further extend its applicability. Overall, the proposed cognitive digital resilience architecture provides a conceptual foundation for cloud environments in which security intelligence, application reliability, and adaptive response operate as interconnected capabilities. Its central contribution is the use of GenAI to transform continuously generated cloud data into contextual intelligence that can support more responsive, explainable, and resilient enterprise security operations.

VI. FUTURE WORK

Future research can extend the proposed framework by developing specialized cognitive GenAI models capable of understanding the unique characteristics of cloud applications, enterprise security policies, infrastructure dependencies, and organizational risk requirements. Retrieval-Augmented Generation can be integrated to ground generated responses in verified threat intelligence, security standards, configuration repositories, incident-response procedures, and organizational knowledge bases. Such an approach could reduce unsupported recommendations and improve the traceability of AI-generated security decisions. Graph-based intelligence is another important research direction because cloud environments contain complex relationships among users, identities, APIs, workloads, containers, services, vulnerabilities, and network connections. Representing these relationships as dynamic security graphs could improve the identification of multi-stage attacks and cascading operational failures. Future research could also investigate multimodal

|www.ijrpetm.com | ISSN: 2454-7875 | editor@ijrpetm.com |A Bimonthly, Peer Reviewed & Scholarly Journal|

||Volume 9, Issue 4, July – August 2026||

DOI:10.15662/IJRPETM.2026.0904011

intelligence capable of analyzing structured telemetry, unstructured logs, configuration files, application traces, and security reports within a unified cognitive architecture. Continual learning mechanisms could allow the system to adapt to changing workload behavior and newly emerging threats without requiring complete retraining. Reinforcement learning may additionally enable autonomous security agents to evaluate the consequences of defensive actions and improve response strategies over time. Such capabilities should be developed within controlled environments where actions can be tested and validated before being applied to production systems. Future work should also focus on the trustworthiness, security, and governance of autonomous GenAI-based resilience systems. Research is needed to address model hallucination, adversarial prompting, data poisoning, malicious telemetry manipulation, model drift, and unauthorized automated actions. Confidence-aware mechanisms could classify generated recommendations according to their reliability and potential impact, allowing low-risk actions to be automated while routing uncertain or high-impact decisions to human security professionals. Privacy-preserving federated learning could enable organizations or cloud domains to collaboratively improve threat intelligence without exchanging sensitive raw telemetry. Future studies should evaluate the framework using real-world cloud workloads, diverse cloud providers, realistic attack simulations, and long-duration operational datasets. Evaluation metrics should include detection effectiveness, false-positive rates, response latency, resilience improvement, computational overhead, scalability, explanation quality, and analyst workload reduction. Cyber ranges and cloud digital twins could provide controlled environments for testing cognitive security agents against evolving attack scenarios. Further research could integrate the framework with zero-trust architectures, autonomous compliance enforcement, confidential computing, software supply-chain security, and post-quantum cryptographic protection. These developments could evolve cognitive digital resilience from an intelligent monitoring capability into a comprehensive adaptive ecosystem that continuously observes cloud environments, reasons about security and operational risks, validates potential responses, and safely supports automated resilience across complex enterprise applications.

REFERENCES

1. Zheng, L., Zhang, J., Wang, X., Lin, F., & Meng, Z. (2024). Multimodal-based abnormal behavior detection method in virtualization environment. ***Computers & Security, 143***, 103908. https://doi.org/10.1016/j.cose.2024.103908
2. Selvarajan, K. (2025). Petabyte-scale data processing for real-time enterprise security analytics. International Research Journal of Innovative Engineering (IRJIE), 9(5), 17566–17576.
3. Jayaraman, S., Rajendran, S., & P, S. P. (2019). Fuzzy c-means clustering and elliptic curve cryptography using privacy preserving in cloud. International Journal of Business Intelligence and Data Mining, 15(3), 273-287.
4. Goyal, K. K., Hebbar, K. S., & Mali, R. K. (2026, March). AI Modernization Enabled by Cloud-Native and Edge-Intelligent Architectures. In International Conference on Information Technology and Artificial Intelligence (pp. 102-114). Cham: Springer Nature Switzerland.
5. Polamarasetty, V. K. (2023). Modern enterprise HR technology through Workday-based benefits and absence management. International Journal of Engineering & Extended Technologies Research (IJEETR), 5(4), 6908–6913.
6. Badam, L. R. (2022). Machine learning-based catastrophic loss prediction for climate-related insurance risk. International Journal of Future Innovative Science and Technology (IJFIST), 5(1), 7797–7807.
7. Aragani, V. M., Maroju, P. K., & Mudunuri, L. N. R. (2024, December). Implementing Non-functional Production Regression Testing with Kubernetes. In International Conference on Information and Communication Technology for Competitive Strategies (pp. 231-244). Singapore: Springer Nature Singapore.
8. Raja, G. V. (2022). AI Enabled Cloud and Data Engineering Frameworks for Secure, Scalable, and Intelligent Cyber Physical Analytics Systems. International Journal of Research and Applied Innovations, 5(4), 7395-7409.
9. Bitragunta, S. L. V. (2025). AI-assisted stability analysis of microgrids with distributed renewable energy sources. International Journal of Advanced Engineering Science and Information Technology, 8(1), 15681–15686.
10. Matrouk, K., V, S., Kumar, S., Bhadla, M. K., Sabirov, M., & Saadh, M. J. (2023). Deep Learning–based Dynamic User Alignment in Social Networks. ACM Journal of Data and Information Quality, 15(3), 1-26.
11. Reddy, K. V. (2024). Accelerating Functional Coverage Closure Through Iterative Machine Learning. Int. J. Comput. Appl. Inf. Technol, 7, 1401-1411.
12. Jayabalan, K., Parmsivan, S., Sunkara, G., Parikh, M., Challa, P., & Nutalapati, V. (2025, November). Innovative framework for secure and scalable web and mobile application development in fintech: A user-centric and AI-driven approach. In 2025 5th International Conference on Ubiquitous Computing and Intelligent Information Systems (ICUIS) (pp. 1499-1505). IEEE.
13. Kavuru, R. R., & Balaji, R. (2023). Extending the service mesh into a compliance enforcement fabric: A policy-aware architecture for regulated financial platforms. International Journal of Emerging Trends in Engineering and Management Research, 8(3), 13612–13618.

|www.ijrpetm.com | ISSN: 2454-7875 | editor@ijrpetm.com |A Bimonthly, Peer Reviewed & Scholarly Journal|

||Volume 9, Issue 4, July – August 2026||

DOI:10.15662/IJRPETM.2026.0904011

14. Chinnam, N. B. (2023). Modernizing retail fulfillment operations through automated load execution and microservices. International Journal of Computer Technology and Electronics Communication, 6(4), 7367–7371.
15. Manda, P. (2026). Database modernization - Sybase to SQL Server migration. International Journal of Engineering & Extended Technologies Research, 8(1), 252–258.
16. Chundi, V. R. K., Agarwal, V., & Arya, P. (2025, November). Green AI for Sustainable Supply Chains: Challenges in Emerging Economies. In *2025 International Conference on Computational Engineering, Sensing Technology and Management (ICCETM)* (pp. 1-5). IEEE.
17. Sudhan, S. K. H. H., & Kumar, S. S. (2016). Gallant Use of Cloud by a Novel Framework of Encrypted Biometric Authentication and Multi Level Data Protection. Indian Journal of Science and Technology, 9, 44.
18. Puram, S. (2026). A Resilient And Integrity-Verified Over-The-Air Software Update Architecture For Software-Defined Vehicles. International Journal of Artificial Intelligence and Machine Learning, 6(5s), 929-936.
19. Gopinathan, V. R. (2023). Modernizing Enterprise Applications Using Intelligent API Frameworks Machine Learning and Cloud Native Computing. International Journal of Science, Research and Technology, 6(5), 10690-10697.
20. Pothuri, M. K. (2026). Predicting Very High-Cost Claimants Using Symmetry ETG/PEG Feature Engineering Combined with Advanced Machine Learning. International Journal of AI, BigData, Computational and Management Studies, 352-357.
21. Soundappan, S. J. (2021). Integrated Artificial Intelligence Framework for Enterprise Cloud Modernization and Intelligent Threat Management Systems. International Journal of Research Publications in Engineering, Technology and Management (IJRPETM), 4(4), 5274-5284.
22. Puli, S. K., & Pichika, P. B. (2024). An Explainable AI Framework for Predictive Clinical Specimen Quality Management and Pre-Analytical Error Detection. European Journal of Advances in Engineering and Technology, 11(11), 131-143.
23. Kavuru, R. R., & Balaji, R. (2023). Extending the service mesh into a compliance enforcement fabric: A policy-aware architecture for regulated financial platforms. International Journal of Emerging Trends in Engineering and Management Research, 8(3), 13612–13618.
24. Ahuja, D. (2026). A Platform Engineering Maturity Model For Cloud-Native Enterprise Transformation. Journal of International Crisis & Risk Communication Research (JICRCR), 9(4), 126.
25. Hashmi, H., & Srikanth, V. (2023, November). Combining Neural Networks to Recognize Offline Digits & Words by Training the Model Using Keras. In 2023 3rd International Conference on Advancement in Electronics & Communication Engineering (AECE) (pp. 694-697). IEEE.
26. Balaraman, N. K., Patel, K., & Reddy, N. (October 2025). Smart Water Management: Integrating PLC and SCADA Technologies for Sustainable Urban Infrastructure. In Proceedings of the 22nd International Conference on Informatics in Control, Automation and Robotics (ICINCO) (Vol. 1, pp. 305–312). SciTePress.
27. Sugumar, R. (2022). Federated Learning and Distributed AI Architectures for Cloud-Based Cyber Healthcare Data Collaboration Systems. International Journal of Future Innovative Science and Technology (IJFIST), 5(5), 9232.
28. Sasikumar, B., Venkatasalam, K., & Rajendran, P. (2024). Induction motor fault detection and classification using rcnn and surf based machine learning algorithms and infrared thermography. Scientia Iranica.
29. Ramasamy, M. (2026). High-availability architecture patterns for enterprise network management platforms. International Journal of Advanced Engineering Science and Information Technology, 9(1), 78–87.
30. Chinnam, N. B. (2023). Modernizing retail fulfillment operations through automated load execution and microservices. International Journal of Computer Technology and Electronics Communication, 6(4), 7367–7371.
31. Mathew, A. (2021). Artificial intelligence and cognitive computing for 6G communications & networks. International Journal of Computer Science and Mobile Computing, 10(3), 26-31.
32. Hashmi, H., & Srikanth, V. (2023, November). Combining Neural Networks to Recognize Offline Digits & Words by Training the Model Using Keras. In 2023 3rd International Conference on Advancement in Electronics & Communication Engineering (AECE) (pp. 694-697). IEEE.
33. Muppidi, N. K. R., Divi, V. R., Gulapalli, S., Rachamalla, S., Tatavarthi, S., & Lakshmi, M. A. (2026, April). CostAgent: Self-Improving Autonomous LLM-Based Orchestration for Cost-Optimal Cloud Data Processing at Scale. In *2026 International Conference on Artificial Intelligence, Systems, and Emerging Technologies (ICAISET)* (pp. 1-6). IEEE.
34. Matrouk, K., V, S., Kumar, S., Bhadla, M. K., Sabirov, M., & Saadh, M. J. (2023). Deep Learning–based Dynamic User Alignment in Social Networks. ACM Journal of Data and Information Quality, 15(3), 1-26.
35. Alzoubi, Y. I., Mishra, A., & Topcu, A. E. (2024). Research trends in deep learning and machine learning for cloud computing security. ***Artificial Intelligence Review, 57***, 132. https://doi.org/10.1007/s10462-024-10776-5